


PO # 1278

Feb. 06, 2017

MAX. DIA. BUOY WATCH CIRCLE = 4.4 N.Miles

Position: 22 40 N, 157 57 W

2.7 m Surlyn Buoy with
 (2) IMET/ARGOS Telemetry w/ Sonic Wind,
 XEOS GPS, SBE 39AT, Lascar At/H
 VAISALA WXT 520, PCO2, SAMI, SBE 16,



HARDWARE DESIGNATION	
(A)	U-Joint, 1" Chain Shackle, 1" EndLink, 3/4" Chain Shackle
(C)	3/4" Chain Shackle, 7/8" EndLink, 3/4" Chain Shackle
(D)	3/4" Chain Shackle, 3/4" Anchor Shackle
(E)	3/4" Anchor Shackle, 7/8" EndLink, 3/4" Anchor Shackle
(G)	5/8" Chain Shackle, 7/8" EndLink, 5/8" Chain Shackle
(H)	5/8" Chain Shackle, 7/8" EndLink, 7/8" Anchor Shackle
(I)	(1) 1.25" Master Link, (1) 5/8" Ch Sh. (1) 7/8" End Link, (1) 7/8" Anc Sh

HARDWARE REQUIRED (Includes Spares)	
(2)	1" Chain Shackles
(1)	1" Anchor Shackles
(2)	1" Weldless End Link
(2)	1.25" Master Link
(6)	7/8" Anchor Shackles
(60)	7/8" Weldless Links
(60)	3/4" Chain Shackles
(5)	3/4" Anchor Shackles
(60)	5/8" Chain Shackles

Top and bottom to be clearly marked.
 Mark Reel for identification
 0.9 m mark "50 meters"
 5.9 m mark "55 meters"
 15.9 m mark "65 meters"
 25.9 m mark "75 meters"
 35.9 m mark "85 meters"
 45.9 m mark "95 meters"
 55.9 m mark "105 meters"
 70.9 m mark "120 meters"

Top and bottom to be clearly marked.
 Mark Reel for identification
 8.5 m mark "135 meters"
 28.5 m mark "155 meters"