



**3 meter Discus Buoy with
2 ASIMET Systems Measuring:
BPR, HRH, WND, SWR, LWR, PRC
And Argos Telemetry**

Note:
Depth of bottom of bridle estimated
@ 2 M with 0.6m of Buoy Freeboard

No Foul on all cages
and instruments above
60 m.

Note: All instruments without cages
have protective trawler guards

Top to be Clearly Marked. Wire should be Marked in 3 places:
9.17 Meters from top eye - Mark should say "60 Meters"
19.17 Meters from top eye - Mark should say "70 Meters"
29.17 Meters from top eye - Mark should say "80 Meters"

Top to be Clearly Marked. Wire should be Marked in 7 places:
4 Meters from top eye - Mark should say "90 Meters"
14 Meters from top eye - Mark should say "100 Meters"
24 Meters from top eye - Mark should say "110 Meters"
34 Meters from top eye - Mark should say "120 Meters"
44 Meters from top eye - Mark should say "130 Meters"
54 Meters from top eye - Mark should say "140 Meters"
64 Meters from top eye - Mark should say "150 Meters"

TERMINATION CODES	
(A)	BRIDLE: U-JOINT, 1" CHAIN SHACKLE 1" ENDLINK, 7/8" CHAIN SHACKLE
(C)	3/4" CHAIN SHACKLE, 7/8" ENDLINK, 3/4" CHAIN SHACKLE
(D)	3/4" CHAIN SHACKLE, 3/4" ANCHOR SHACKLE
(E)	3/4" ANCHOR SHACKLE, 7/8" ENDLINK, 3/4" ANCHOR SHACKLE
(G)	5/8" CHAIN SHACKLE, 7/8" ENDLINK, 5/8" CHAIN SHACKLE
(H)	5/8" CHAIN SHACKLE, 7/8" ENDLINK, 7/8" ANCHOR SHACKLE

HARDWARE REQUIRED (INCLUDES APPROX. 20% SPARES)	
1" CHAIN SHACKLES	2
1" WELDLESS END LINK	2
7/8" ANCHOR SHACKLES	5
7/8" CHAIN SHACKLES	2
7/8" WELDLESS LINKS	48
3/4" CHAIN SHACKLES	66
3/4" ANCHOR SHACKLES	14
5/8" CHAIN SHACKLES	15

ANCHOR (DEPTH - 5000 M.) WET WT. 5000 LBS (AIR WT. 5814 LBS)

* Note: Unless water depth is more than 100 meters different than shown
the length of this shot should remain 500 meters.

**NTAS-4 MOORING
Fourth Deployment**

Revision 1